## 25-Pair F-F CAT 3 Telco Cable Assembly



## Package Include:

A. 25-Pair Female-Female CAT 3 Telco
Cable Assembly, 1 Piece

## **Features and Benefits**

- Designed to be use for voice and low speed data applications with punch down blocks, patch panels, and distribution boxes
- Can be used as an extension cables
- 24 AWG unshielded twisted pair (UTP) Category 3 rated cable
- Includes one 50-pin female connectors (RJ21)
- Available in 5, 10, 15, 25 feet

Part No: ICPCSTFFxx Rev: H Page 1 of 2



© Copyright 2015, ICC. This document and the designs, specifications and information contained herein are the property of ICC. Reproduction, modification, alteration or unauthorized use without ICC's approval is strictly prohibited. ICC and the ICC logo are registered trade name and trademark of ICC. All rights reserved.

					1100		oomoation	
		PIN 26						
$\left  - \right $					PIN 25			
				<b></b>	<u>,                                    </u>	<del></del>	<b>.</b> ,	·]
$\downarrow \downarrow$	⊥⊥ ∣ "L" <u>+.</u>			25	Violet/Gray	50	Gray/Violet	25
$\prod_{i=1}^{n}$			ļ	24	Violet/Brown	49	Brown/Violet	24
			ļ	23	Violet/Green	48	Green/Violet	23
	IC POSIFIC		!	22	Violet/Orange	47	Orange/Violet	22
			!	21	Violet/Blue	46	Blue/Violet	21
	, P		ļ	20	Yellow/Gray	45	Gray/Yellow	20
		·	·, !	19	Yellow/Brown	44	Brown/Yellow	19
		Item No.	Length (FT)	18	Yellow/Green	43	Green/Yellow	18
		ICPCSTFF05	5	17	Yellow/Orange	42	Orange/Yellow	17
		ICPCSTFF10	10	16	Yellow/Blue	41	Blue/Yellow	16
		ICPCSTFF15	15	15	Yellow/Gray	40	Gray/Black	15
$\checkmark$		ICPCSTFF25	25	14	Black/Brown	39	Brown/Black	14
<u>NOTE: UI</u>	NLESS OTHERWI	ISE SPECIFIED		13	Black/Green	38	Green/Black	13
1. Female 5 <sup>r</sup>	0-Pin Telco Connecto	ors:	ţ	12	Black/Orange	37	Orange/Black	12
A. Mate	erial:		ł	11	Black/Blue	36	Blue/Black	11
-+	High Strength Copper	Alloy Contacts	ł	10	Red/Blue	35	Gray/Red	10
-+	High Impact Thermo P	Plastic Housing And	Cover	9	Red/Gray	34	Brown/Red	9
B. Finis	ish: 30 Micro-inches of	f Gold over Nickel p	plating	8	Red/Brown	33	Green/Red	8
	in mating contact a	area	ł	7	Red/Orange	32	Orange/Red	7
C. Cold	or: Black		ł	6	Red/Blue	31	Blue/Red	6
2. 25-Pair C	CAT 3 Telco Cable:		ļ	5	White/Gray	30	Gray/White	5
A. Mate	erial:		ļ	4	White/Brown	29	Brown/White	4
-2	24 AWG Solid Copper	r Conductors	!	4	White/Green	29	Green/White	4
-F	PVC Insulation and Ja	acket	ļ	3 2	White/Orange	28	Orange/White	2
-CMR					<u> </u>		-	
B. Cold	or: Gray		!	1	White/Blue	26 DIN	Blue/White	1 DINI
C. Len	ngth: XX: 05-5 Feet, 10	J-10 Feet, 15-15 Fe	et, 25-25 Feet	PAIR	BODY (TIP)	PIN		PIN
3. Country o	of Origin: China		ļ	NO.	]		(RING)	<u> </u>
			!	<u> </u>		WIRE	COLOR	
Rev: H Page 2 c			C icc.com csr@		1 5	Ŷ	C	
	<ol><li>ICC. This document and the designs, sp thorized use without ICC's approval is strictly</li></ol>				,			